



Product Family Code

E1.10.3.1.0097



Product Features

Mounting Location	Ceiling
Mounting Type	Buffle Ceiling Mounted
Light Source	COB LED
Optic	Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP20
Origin	Turkey
Warranty	Up to 5 Years

Light Output

Adjustability	Adjustable
Light Distribution	Direct
Tilt Angle	-15° / +15°

Dimension

Width	80 mm	80 mm
Lenght	150 mm	150 mm
Height	150 mm	200 mm

Electrical Data

Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	I
Driver (Included)	Osram
Led	Samsung
Dimming	Optional (Depends On Driver)

Performance Data

Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115

A LIGHT SOURCE	B DIMENSIONS	C LIGHT COLOR	D POWER	E CONTROL	F BODY COLOR	G BODY FINISH	H OPTIC	I EMERGENCY KIT
1 LED	1 A:80mm X B:150mm X H:150 2 A:80mm X B:150mm X H:200	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90 13 T.WHITE	2006 2x6 Watt 2007 2x7 Watt 2010 2x10 Watt 2012 2x12 Watt 2014 2x14 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	24 24° 36 36°	9 W/O KIT

Other Features

EXAMPLE CODE: E1.10.3.1.0097_1.1.6.2006.1.2.2.24.9